



## Material Safety Data Sheet

The Valvoline Company

Date Prepared: 08/04/98  
Date Printed: 10/18/99  
MSDS No: 503.0177862-007.0011

NAPA DIESEL FUEL ANTI-GEL & CONDITIONER

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### Material Identity

Product Name: NAPA DIESEL FUEL ANTI-GEL & CONDITIONER  
General or Generic ID: FUEL TREATMENT

#### Company

The Valvoline Company  
P.O. Box 14000  
Lexington, KY 40512

#### Telephone Numbers

Emergency: 1-800-274-5263  
Information: 1-606-357-7847

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
KEROSENE	8008-20-6	88.0- 98.0
FUEL ADDITIVE		0.0- 8.0

### 3. HAZARDS IDENTIFICATION

#### Potential Health Effects

##### Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: blurred vision

##### Skin

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

##### Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

##### Inhalation

Breathing of vapor or mist is possible.

##### Symptoms of Exposure

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea,

headache, unconsciousness), and death.

Target Organ Effects  
No data

Developmental Information  
No data

Cancer Information  
This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

Other Health Effects  
No data

Primary Route(s) of Entry  
Inhalation, Skin contact.

---

#### 4. FIRST AID MEASURES

##### Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

##### Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

##### Swallowing

Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Seek medical attention. If possible, do not leave individual unattended.

##### Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians  
No data

---

#### 5. FIRE FIGHTING MEASURES

Flash Point  
> 120.0 F (48.8 C) PMCC

Explosive Limit  
(for component) Lower .7

Autoignition Temperature  
No data

Unstable Products of Combustion

## HAZARDOUS PRODUCTS OF COMBUSTION

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

## Fire and Explosion Hazards

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

## Extinguishing Media

regular foam, carbon dioxide, dry chemical.

## Fire Fighting Instructions

Water or foam may cause frothing which can be violent and possibly endanger the life of the firefighter. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

## NFPA Rating

Health - 1, Flammability - 2, Reactivity - 0

---

## 6. ACCIDENTAL RELEASE MEASURES

## Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

## Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

---

## 7. HANDLING AND STORAGE

## Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five gallon pails and larger metal containers including tank cars and tank trucks should be grounded and/or bonded when material is transferred.

## Storage

Not applicable

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

## Skin Protection

Wear resistant gloves such as: neoprene, To prevent repeated or prolonged skin contact, wear impervious clothing and boots..

## Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

## Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

## Exposure Guidelines

## Component

KEROSENE (8008-20-6)

No exposure limits established

FUEL ADDITIVE

No exposure limits established

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Boiling Point

(for component) > 300.0 F (148.8 C)

## Vapor Pressure

(for component) 5.000 mmHg

## Specific Vapor Density

> 1.000 @ AIR=1

## Specific Gravity

.800 - .820 @ 77.00 F

## Liquid Density

6.750 lbs/gal @ 77.00 F  
.832 kg/l @ 25.00 C

## Percent Volatiles (Including Water)

85.0 - 100.0 %

## Evaporation Rate

SLOWER THAN ETHYL ETHER

## Appearance

HAZY

## State

LIQUID

## LIQUID

Physical Form

No data

Color

YELLOW

Odor

No data

pH

Not applicable

---

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: strong oxidizing agents.

---

11. TOXICOLOGICAL INFORMATION

No data

---

12. ECOLOGICAL INFORMATION

No data

---

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

FLAMMABLE LIQUIDS, N.O.S., 3, UN 1993, III

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

KEROSENE

RQ (Reportable Quantity) - 49 CFR 172.101  
Not applicable

---

#### 15. REGULATORY INFORMATION

##### US Federal Regulations

TSCA (Toxic Substances Control Act) Status  
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4  
None

SARA 302 Components - 40 CFR 355 Appendix A  
None

Section 311/312 Hazard Class - 40 CFR 370.2  
Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden  
Release of Pressure( )

SARA 313 Components - 40 CFR 372.65  
None

##### International Regulations

Inventory Status  
EINECS (EUROPE) The intentional ingredients of this product are listed.

##### State and Local Regulations

California Proposition 65  
None

New Jersey RTK Label Information  
KEROSENE

8008-20-6

Pennsylvania RTK Label Information  
KEROSINE (PETROLEUM)

8008-20-6

---

#### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last Page



Remove from My List



Download