

CUSTOM-PAK PRODUCTS INC -- 39C014N-12 AEROSOL PAINT -- 8010-00F057115

=====  
Product Identification  
=====

Product ID:39C014N-12 AEROSOL PAINT  
MSDS Date:04/10/1991  
FSC:8010  
NIIN:00F057115  
Status Code:A  
MSDS Number: CJBFY  
=== Responsible Party ===  
Company Name:CUSTOM-PAK PRODUCTS INC  
Address:N115 W19150 EDISON DRIVE  
City:GERMANTOWN  
State:WI  
ZIP:53022-5000  
Country:US  
Info Phone Num:414-251-6180  
Emergency Phone Num:414-251-6180  
Preparer's Name:W C BRADLEY  
CAGE:CUSTM  
=== Contractor Identification ===  
Company Name:CUSTOM-PAK PRODUCTS, INC.  
Address:N115 W19150 EDISON DRIVE  
Box:City:GERMANTOWN  
State:WI  
ZIP:53022  
Country:US  
Phone:414-251-6180  
CAGE:CUSTM

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACETONE; DIMETHYL KETONE; 2-PROPANONE \*98-3\*  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 20%  
OSHA PEL:2400 MG/CUM  
ACGIH TLV:750 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH  
AROMATIC NAPHTHA, C8&10 AROMATIC HYDROCARBON \*98-3\*  
CAS:64742-95-6  
RTECS #:WF3400000  
Fraction by Wt: 2%

Ingred Name:PROPANE (DIMETHYLMETHANE) \*98-3\*  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 13.64%  
Other REC Limits:1800 MG/CUM  
OSHA PEL:1000 PPM  
ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:ISOBUTANE, 2-METHYLPROPANE  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 8.36%  
Other REC Limits:1000 PPM  
OSHA PEL:1800 MG/CUM  
ACGIH TLV:1000 PPM

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) \*98-3\*  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 11.31%  
Other REC Limits:100 PPM  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM, SKIN  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE,TOLUOL (IARC CARC- GROUP 3) \*98-3\*  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 6.46%  
Other REC Limits:375 MG/CUM

OSHA PEL:100 PPM  
ACGIH TLV:100 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES  
MINERAL SPIRITS \*98-3\*

CAS:64742-88-7  
Fraction by Wt: 1.75%  
Other REC Limits:100 PPM  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

Ingred Name:BUTANOL, N-BUTYL ALCOHOL, PROPYL CARBINOL, BUTYL ALCOHOL  
\*98-3\*

CAS:71-36-3  
RTECS #:E01400000  
Fraction by Wt: 1.7%  
Other REC Limits:300 MG/CUM  
OSHA PEL:100 PPM  
ACGIH TLV:C 152 MG/CUM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOLATILE ORGANIC CONTENT: 4.91  
RTECS #:9999999VO

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC EFFECT.  
IRRITATION OF THE RESPIRATORY TRACT/NERVOUS SYSTEM DEPRESSION.  
EYES: IRRITATION, BLURRED VISION. SKIN: IRRITATION. INGESTION: MAY  
BE HARMFUL/FATAL IF SWALLOWED. REPEATED /PROLONGED OVEREXPOSURE TO  
SOLVENTS MAYCAUSE DAMAGE TO LIVER, KIDNEYS, BRAIN & NERVOUS SYSTEM.  
(SEE SUPP)

Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, STAGGERING  
GAIT, CONFUSION, UNCONSCIOUSNESS, COMA, REDNESS, TEARING,  
DRYING/CRACKING OF SKIN  
Medical Cond Aggravated by Exposure:ASTHMA & OTHER RESPIRATORY  
AILMENTS. CHEMICAL SENSITIZATION.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE FROM EXPOSURE. GIVE OXYGEN IF NEEDED.  
EYES: IMMEDIATELY FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP &  
WATER. INGESTION: DRINK 1-2 GLASSES OF WATER TO DILUTE. DON'T  
INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Flash Point:12F  
Extinguishing Media:CO2/FOAM  
Fire Fighting Procedures:FIGHT FIRE FROM SAFE DISTANCE. WEAR FULL  
PROTECTIVE EQUIPMENT W/SELF CONTAINED BREATHING APPARATUS. WATER  
MAY BE USED TO COOL RUPTURED CONTAINERS.  
Unusual Fire/Explosion Hazard:PRESSURE BUILDUP DUE TO HEAT EXPOSURE MAY  
CAUSE CONTAINERS TO EXPLODE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. PROVIDE  
VENTILATION. COLLECT W/ABSORBENT MATERIALS & NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DON'T STORE IN AREAS >100F/NEAR  
FIRE/OPEN FLAME. WHEN STORING LARGE QUANTITIES, STORAGE CONDITIONS  
SHOULD COMPLY W/OSHA 1910.106.  
Other Precautions:PREVENT PROLONGED/REPEATED BREATHING OF VAPOR/SPRAY  
MIST. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. USE  
W/ADEQUATE VENTILATION.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IN OPEN AREAS W/UNRESTRICTED VENTILATION, USE A  
NIOSH/MSHA APPROVED RESPIRATOR TO REMOVE AIRBORNE PARTICLES OF  
OVERSPRAY. W/RESTRICTED VENTILATION, USE AN APPROVED  
CHEMICAL/MECHANICAL FILTER DESIGNED TO REMOVE PARTICLES/ORGANIC

VAPORS.

Ventilation:SUFFICIENT TO KEEP AIR CONTAMINANT BELOW CURRENT OSHA  
PEL/ACGIH TLV.

Protective Gloves:REQUIRED

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING & SHOES  
BEFORE REUSE. WASH HANDS BEFORE EATING/USING WASHROOM.

Supplemental Safety and Health

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE  
CONTENTS MAY BE HARMFUL/FATAL.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:-43 TO 340F

Vapor Density:>1

Evaporation Rate & Reference:FASTER THAN ETHER

Solubility in Water:<0.1

Appearance and Odor:OPAQUE SPRAY W/SOLVENT ODOR

Percent Volatiles by Volume:80-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME/HEAT  
EXPOSURES

Hazardous Decomposition Products:CO2, CO

===== Disposal Considerations =====

Waste Disposal Methods:DON'T INCINERATE CONTAINERS. DISPOSE OF IN  
ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.