



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set  
**Product Use:** Adhesive.  
**Manufacturer/Supplier:** Custom Building Products  
13001 Seal Beach Blvd  
Seal Beach, CA90740  
**Phone Number:** (562) 598-8808  
**Emergency Phone:** INFOTRAC 1-800-535-5053 (US and Canada)  
INTERNATIONAL + 1-352-323-3500  
**Date of Preparation:** April 12, 2012 **Revision Date:** September 13, 2012

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

CAUTION

IRRITATING TO EYES. MAY CAUSE SKIN IRRITATION.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, skin absorption, eye contact, inhalation, and ingestion.

**Eye:** Irritating to eyes.

**Skin:** May cause skin irritation.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Medical Conditions Aggravated By Exposure:** Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

**Target Organs:** Skin, eyes, gastrointestinal tract and respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Stoddard solvent	8052-41-3	1 - 5
1,3,5-Trimethylbenzene	108-67-8	≤ 0.1
1,2,4-Trimethylbenzene	95-63-6	≤ 0.1
Calcium carbonate	1317-65-3	30 - 60
Silica, crystalline, quartz	14808-60-7	≤ 0.1
Ethylene glycol	107-21-1	1 - 5



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

## Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
  - Unsuitable Extinguishing Media:** Not available.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
  - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
- Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Scoop up material and place in a disposal container. Provide ventilation.
- Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

- Handling:**  
Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

**Storage:**

Keep out of the reach of children. Keep container tightly closed and dry. Store in a cool place. Keep from freezing.

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines**

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Stoddard solvent	100 ppm	100 ppm
1,3,5-Trimethylbenzene	Not available.	25 ppm
1,2,4-Trimethylbenzene	Not available.	Not available.
Calcium carbonate	15 mg/m <sup>3</sup> (total); 5 mg/m <sup>3</sup> (resp) ((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)); ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)); ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	10 mg/m <sup>3</sup>
Silica, crystalline, quartz		0.025 mg/m <sup>3</sup>
Ethylene glycol	50 ppm	50 ppm

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

**Personal Protective Equipment:**

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Paste-like compound.
<b>Color:</b>	White.
<b>Odor:</b>	Mild acrylic.
<b>Odor Threshold:</b>	Not available.
<b>Physical State:</b>	Paste.
<b>pH:</b>	8.5-9.3
<b>Viscosity:</b>	550K – 630K cps
<b>Freezing Point:</b>	~ 0 °C (~ 32 °F)
<b>Boiling Point:</b>	Not available.
<b>Flash Point:</b>	Not available.
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	Not available.
<b>Vapor Density:</b>	Not available.



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

<b>Relative Density:</b>	~ 1.4 g/mL.
<b>Solubility in Water:</b>	Partially Miscible.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.
<b>Percent Volatile, wt. %:</b>	~ 30%
<b>VOC content :</b>	< 60 g/L.

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Strong oxidizers.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

<b>Ingredient</b>	<b>LD<sub>50</sub> (oral)</b>	<b>LC<sub>50</sub></b>
Stoddard solvent	> 5000 mg/kg, rat	Not available.
1,3,5-Trimethylbenzene	5000 mg/kg, rat	24000 mg/m <sup>3</sup> 4hr, rat
1,2,4-Trimethylbenzene	3400 mg/kg, rat	18000 mg/m <sup>3</sup> 4hr, rat
Calcium carbonate	6450 mg/kg, rat	Not available.
Silica, crystalline, quartz	120 g/kg, rat (TD <sub>10</sub> )	Not available.
Ethylene glycol	4000 mg/kg, rat	Not available.

**Eye:** Irritating to eyes. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

### EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Ingestion of ethylene glycol in large amounts can cause liver, kidney and brain damage.

**Chronic Effects:** Not hazardous by WHMIS/OSHA criteria.

**Carcinogenicity:** Hazardous by WHMIS/OSHA criteria.

<b>Ingredient</b>	<b>Chemical Listed as Carcinogen or Potential Carcinogen *</b>
Stoddard solvent	Not listed.
1,3,5-Trimethylbenzene	Not listed.
1,2,4-Trimethylbenzene	Not listed.
Calcium carbonate	Not listed.
Silica, crystalline, quartz	G-A2, I-1, N-1, CP65
Ethylene glycol	G-A4

\* See Section 15 for more information.



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Not hazardous by WHMIS/OSHA criteria.

**Developmental Effects:**

**Teratogenicity:** Hazardous by WHMIS/OSHA criteria.

**Embryotoxicity:** Hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### DOT Ground Classification

Not regulated

### TDG Ground Classification

Not regulated

### IATA Classification

Not regulated

### IMDG Classification

Not regulated

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

### SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Stoddard solvent	Not listed.	Not listed.	Not listed.	Not listed.
1,3,5-Trimethylbenzene	Not listed.	Not listed.	Not listed.	Not listed.
1,2,4-Trimethylbenzene	Not listed.	Not listed.	Not listed.	313
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol	Not listed.	Not listed.	5,000	313



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

## State Regulations

**New Jersey Right-To-Know:** Calcium carbonate, Ethylene glycol, Stoddard solvent, Silica Quartz. **Pennsylvania Right-To-Know:** Limestone, 1,2-Ethandiol, Stoddard solvent, Sodium hydroxide, Pseudocumene, Benzene, dimethyl-, Benzene, ethyl-. **Massachusetts Right-To-Know:** Calcium carbonate, Ethylene glycol, Stoddard solvent.

## California Proposition 65:

This product contains chemicals known to the State of California to cause cancer.

## Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Stoddard solvent	DSL	Yes.
1,3,5-Trimethylbenzene	DSL	Yes.
1,2,4-Trimethylbenzene	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Ethylene glycol	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

## HMIS - Hazardous Materials Identification System

Health - 1\*      Flammability - 0      Physical Hazard - 0      PPE – B

## NFPA - National Fire Protection Association:

Health - 1      Fire - 0      Reactivity - 0

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

## WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2B - Skin/Eye Irritant

## WHMIS Hazard Symbols:



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

- OSHA (O)** Occupational Safety and Health Administration.
- ACGIH (G)** American Conference of Governmental Industrial Hygienists.
  - A1 - Confirmed human carcinogen.
  - A2 - Suspected human carcinogen.
  - A3 - Animal carcinogen.
  - A4 - Not classifiable as a human carcinogen.
  - A5 - Not suspected as a human carcinogen.
- IARC (I)** International Agency for Research on Cancer.
  - 1 - The agent (mixture) is carcinogenic to humans.
  - 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
  - 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
  - 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
  - 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
- NTP (N)** National Toxicology Program.
  - 1 - Known to be carcinogens.
  - 2 - Reasonably anticipated to be carcinogens.



# MATERIAL SAFETY DATA SHEET

ReliaBond Ceramic Tile Mastic and ReliaBond Extended Set

## Section 16: OTHER INFORMATION

**Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** September 13, 2015

**Version #:** 1.1

**Prepared by:** Nexreg Compliance Inc.  
Phone: (519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)