


MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION					
PRODUCT NAME: SnowPrint Wax™		DATE: August 1, 2011		PRODUCT NUMBER(S): 4-1005 (1005709)	
TRADE NAME: Impression Wax, Snow Print Wax. GENERAL USE: Snow print wax CHEMICAL FAMILY: Wax dissolved in Organic solvents. PRODUCT DESCRIPTION: Red liquid with strong, fruit odor.					
MANUFACTURED FOR: Safariland LLC		DATE PREPARED: August 1, 2011		SUPERSEDES: September 23, 2008	
ADDRESS (NUMBER, STREET, P.O. BOX) 13386 International Parkway		TELEPHONE NUMBER FOR INFORMATION / Customer Service 800-347-1200			
(CITY, STATE AND ZIP CODE) Jacksonville, FL 32218		COUNTRY USA		CHEMTEL 24-HOUR EMERGENCY TELEPHONE NUMBER  1-800-255-3924 01-813-248-0585 North America Toll Free International	
SECTION 2 - HAZARDS IDENTIFICATION					
EMERGENCY OVERVIEW May cause mild to severe eye irritation. May cause drying of the skin. Vapors are irritating to nasal passages and throat.					
POTENTIAL HEALTH EFFECTS					
INHALATION: Vapors are irritating to nasal passages and throat. Stupor, headaches, drowsiness, respiratory tract irritation, dryness of skin, unconsciousness.					
SKIN: May cause drying of the skin.					
EYES: May cause mild to severe eye irritation.					
INGESTION: Stupor, headaches, drowsiness, respiratory tract irritation, dryness of skin, unconsciousness. Risk of aspiration if vomiting.					
CARCINOGENICITY:					
NTP? NO		IARC MONOGRAPHS? NO		OSHA REGULATED? NO	
CALIFORNIA, Prop.65? NO					
SECTION 3 - HAZARDOUS INGREDIENTS					
Hazardous Components	% (by Weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES (Full Text Section 15)
Ethyl Acetate	< 9%	141-78-6	205-500-4	F, Xn, Xi	R11,R36,R66,R67
Dimethyl Ether	<72%	115-10-6	204-065-8	F+	R12
Notes: Hazard symbols and risk phrases based on maximum listed concentration of each hazardous ingredient.					
SECTION 4 - FIRST AID MEASURES					
INHALATION: Provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Seek medical attention.					
EYES: Flush with water for 15 minutes. Call a physician if symptoms persist.					
SKIN: Thoroughly wash exposed area.					
INGESTION: Do not induce vomiting as risk of aspiration and chemical pneumonia exists with this product's ingestion. Call a physician immediately. If vomiting, keep patients head below waist to reduce aspiration risk.					

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SnowPrint Wax™
PRODUCT NUMBER(S): 4-1005 (1005709) **DATE:** August 1, 2011

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS:

Aerosols will burst at temperatures above 130 degrees F. Containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure build-up which could result in container rupture.

EXTINGUISHING MEDIA:

Water fog, alcohol foam, dry chemical, CO2.

FIRE FIGHTING PROCEDURES:

Wear SCBA. If aerosols are bursting, stay clear until bursting is completed. Aerosols can be projectiles when bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Aerosols will burst at temperatures above 130 degrees F. Containers exposed to intense heat from fires must be cooled with water to prevent vapor pressure build-up which could result in container rupture.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon Monoxide, Carbon Dioxide, Organic compounds.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wipe up immediately with towel. Ventilate area if needed and wear NIOSH/MSA or European EN-149 approved organic vapor respirator protection.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a cool well ventilated area, away from sources of ignition, and incompatible materials such as strong oxidizers. Avoid use in enclosed areas without respiratory protection and do not breathe concentrated vapors.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH		OSHA	
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TLV/TWA ppm	TWA mg/m3	PEL ppm	PEL mg/m3
Ethyl Acetate	400			2000 IDLH	400		400	1400
Dimethyl Ether	NE			NE	1000		NE	NE

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

NIOSH/MSA or European approved organic vapor respirator if concentrations exceed exposure limits. Area ventilation to keep vapor concentrations within published limits.

PROTECTIVE GLOVES:

Chemical resistant nitrile or neoprene gloves.

EYE PROTECTION:

Safety glasses with side shields for splash protection or chemical goggles if contact with eyes likely.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Protective apron recommended.

WORK / HYGIENIC PRACTICES:

Wash affected skin and surfaces well with soap and water after use of product.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Red liquid with strong, fruit odor.	VAPOR PRESSURE NR
VOC NR Volatility <20	SPECIFIC GRAVITY (WATER = 1) NR
BOILING POINT / BOILING RANGE NR	SOLUBILITY IN WATER 9%
FLASH POINT <0°C	VISCOSITY NR
FLAMMABLE LIMITS LEL: NR UEL: NR	VAPOR DENSITY (AIR = 1) >1
AUTOIGNITION TEMPERATURE NR	EVAPORATION RATE BUTYL ACETATE = 1) >1

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SnowPrint Wax™
PRODUCT NUMBER(S): 4-1005 (1005709) **DATE:** August 1, 2011

SECTION 10 - STABILITY AND REACTIVITY

STABILITY	STABLE	X	CONDITIONS TO AVOID: Temperatures above 130°F, do not puncture or incinerate containers (may burst).
-----------	--------	----------	---

INCOMPATIBILITY (MATERIALS TO AVOID):
 Strong oxidizing and reducing agents, strong acids and bases.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:
 Carbon Monoxide, Carbon Dioxide, Organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.	CONDITIONS TO AVOID: None related to polymerization.
---	--

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Ethyl Acetate	141-78-6	Oral, mouse: LD50 = 4100 mg/kg	Inhalation, mouse: LC50 = 45 gm/m3/2H
	205-500-4		
Dimethyl Ether	115-10-6	Probable LD (oral, human) = 0.5-5 g/kg	LC50 (inhalation, rat) = 164,000 ppm/4H.
	204-065-8		

SECTION 12 - ECOLOGICAL INFORMATION

For Ethyl Acetate: Ecotoxicity: Fish: Fathead Minnow: 230mg/L; 96H; Daphnid LC50=2500 mg/L/96H Golden orfe LC50=270 mg/L/48H
 Environmental: Terrestrial: Expected to have high mobility in soil. Volatilization of Ethyl Acetate from moist soil surfaces is expected to be important.
 Aquatic: Not expected to adsorb to suspended solids and sediment in water. Atmospheric: Expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase Ethyl Acetate is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 10 days.
 Physical: Substance biodegrades at a high rate with little bioconcentration.

For Dimethyl Ether: ENVIRONMENTAL STABILITY: This gas will be dissipated rapidly in well-ventilated areas. Additional environmental data are available for Dimethyl Ether as follows:
 Solubility: 35,300 mg/L in water at 25°C. Biodegradation: May be resistant to biodegradation, based on other ethers; estimated half-life = 2-15 days. Bioconcentration: BCF (Bioconcentration Factor) of 1.7 (estimated). Based on this BCF, Dimethyl Ether is not expected to bioconcentrate in aquatic organisms. Log Kow = 0.10, 0.12.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: This gas can be harmful to animal life. Suspected anesthetic effect on a variety of test animals during clinical studies indicate adverse effects on the central nervous system, liver and cardiovascular system. No information is currently available concerning adverse effects expected to occur to plant-life. Plants may be damaged by frost produced in the presence of rapidly expanding gases.

EFFECT OF CHEMICAL ON AQUATIC LIFE: Aquatic toxicity data are available for Dimethyl Ether, as follows:

- LC50 (Daphnia) = 1852 mg/L, 96 hours
- LC50 (fathead minnow) = 2695 mg/L, 96 hours
- LC50 (rainbow trout) = 3082 mg/L, 96 hours
- LC50 (catfish) = 2419 mg/L, 96 hours
- LC50 (goldfish) = 3677 mg/L, 96 hours
- LC50 (bluegill) = 3429 mg/L, 96 hours
- LC50 (mosquito fish) = 2978 mg/L, 96 hours

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:
 Dispose as hazardous waste by a properly permitted facility, do not discharge into drains or other watercourses. Dispose in accordance with all local, state and federal laws and ordinances.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols, flammable DOT HAZARD CLASS / Pack Group: Aerosol, flammable, 2.1 REFERENCE: 49CFR UN / NA IDENTIFICATION NUMBER: UN 1950 LABEL: Flammable Gas 2.1 HAZARD SYMBOLS:	
IATA HAZARD CLASS / Pack Group: Flammable Gas, 2.1, Aerosol IMDG HAZARD CLASS: 2.1, Flammable Gas, Aerosol RID/ADR Dangerous Goods Code: Un 1950 Aerosol, flammable, 2.1 UN TDG Class / Pack Group: UN 1950, 2.1 /Aerosol Hazard Identification Number (HIN): 23	

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.


MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SnowPrint Wax™
PRODUCT NUMBER(S): 4-1005 (1005709) **DATE:** August 1, 2011

SECTION 15 - REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act): Listed.
SARA TITLE III (USA - Superfund Amendments and Reauthorization Act):
 Acute Health: **Yes** Chronic Health: **Yes**
 Fire: **Yes** Sudden Release of Pressure: **NO**
 Reactive: **NO**

313 REPORTABLE INGREDIENTS: None reportable.
CERCLA (USA - Comprehensive Response Compensation and Liability Act): **CAS# 141-78-6: 5000 lb final RQ; 2270 kg final RQ.**
 California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986: **Not listed.**
 State Right to Know: **Ethyl Acetate: MA, NJ, PA. Dimethyl Ether: MA, NJ, PA.**
CIDL (Canadian Ingredient Disclosure List): Listed.
CDSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List): Listed.
EINECS (European Inventory of Existing Commercial Chemical Substances): Referenced.
WGK Water Quality Index: 1

RISK PHRASES:	SYMBOL(S) REQUIRED FOR EU LABEL	SAFETY PHRASES:
R12: Extremely Flammable R36: Irritating to eyes. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapors may cause drowsiness and dizziness.	 F+ - Extremely Flammable	S2: Keep out of the reach of children. S16: Keep away from ignition - No smoking. S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S33: Take precautionary measures against static discharges.
	 Xn/Xi -Harmful Irritant	

SECTION 16 - OTHER INFORMATION

Legend:

N/A = Not Applicable	N/D = Not Determined	N/E = Not Established	N/R = Not Reported
----------------------	----------------------	-----------------------	--------------------

HMIS HAZARD RATINGS	HEALTH:	1	0 = INSIGNIFICANT
	FLAMMABILITY:	4	1 = SLIGHT
	PHYSICAL HAZARD:	1	2 = MODERATE
	PERSONAL PROTECTIVE EQUIPMENT:		3 = HIGH
			4 = EXTREME

REVISION SUMMARY:
 Revised to EU protocols 8/1/2011, supersedes 9/23/2008 JTV

MSDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com



The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.