

MATERIAL SAFETY DATA SHEET
COATINGS AND RESINS GROUP

PPG Industries, Inc.

SECTION 1 - CHEMICAL, PRODUCT, AND COMPANY INFORMATION

PRODUCT CODE/IDENTITY: 54-330

PRODUCT TRADE NAME: SAFETY YELLOW GLOSS ENAMEL

REVISION DATE: 10/28/02 (000) 0814

CUSTOMER PART #/NAME: Not applicable

CHEMICAL FAMILY: Alkyd

EMERGENCY MEDICAL/SPILL INFO: (304) 843-1300 (U.S.) 01-800-00-21-400 (MEXICO)

TECHNICAL INFORMATION: 1-800-441-9695

PRODUCT SAFETY/MSDS INFORMATION: 4325 ROSANNA DRIVE ALLISON PARK, PA 15101 (412) 492-5555

DATE OF MSDS PREPARATION: 10/22/03

PRIMARY HAZARD WARNING

Combustible. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Harmful if swallowed. May cause slight skin irritation. Causes eye irritation. Vapor and/or spray mist may be harmful if inhaled.

THIS MATERIAL SAFETY DATA SHEET HAS BEEN PREPARED IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200), THE SUPPLIER NOTIFICATION REQUIREMENTS OF SARA TITLE III, SECTION 313, AND OTHER APPLICABLE RIGHT-TO-KNOW REGULATIONS.

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

REF	HAZARDOUS INGREDIENTS	PERCENT	CAS NUMBER	CARCINOGEN*
01	ETHYL BENZENE	0.1- <1	100-41-4	I
02	XYLENES	1 - <5	1330-20-7	
03	ALUMINUM SILICATE	10- <20	1332-58-7	
04	TITANIUM DIOXIDE	5 - <10	13463-67-7	
05	COBALT NEODECANOATE	0.1- <1	27253-31-2	
06	V.M. AND P. NAPHTHA	1 - <5	8032-32-4	
07	NAPHTHA	20- <30	8052-41-3	
08	METHYL ETHYL KETOXIME	0.1- <1	96-29-7	

* Carcinogens: O=OSHA; A=ACGIH; N=NTP; I=IARC

SARA TITLE III & CERCLA CLASSIFICATIONS

REF	CERCLA HAZARDOUS SUBSTANCE RQ (LBS)	SARA EXTREMELY HAZ SUBSTANCE TPQ (LBS)	SARA 313	SARA 311/312				
				AC	CH	FL	PR	RE
01	1000 lbs	NOT ESTAB	Y	Y	Y	Y	N	N
02	100 lbs	NOT ESTAB	Y	Y	N	Y	N	N
03	NOT ESTAB	NOT ESTAB	N	N	N	N	N	N
03	NOT ESTAB	NOT ESTAB	N					(NUSANCDUST)
04	NOT ESTAB	NOT ESTAB	N	N	N	N	N	N
04	NOT ESTAB	NOT ESTAB	N					(TI COMPS)
04	NOT ESTAB	NOT ESTAB	N					(AS TI)
05	NOT ESTAB	NOT ESTAB	N	Y	Y	N	N	N
05	NOT ESTAB	NOT ESTAB	Y					(CO CMPD)

05	NOT ESTAB	NOT ESTAB	Y				(AS CO)
06	NOT ESTAB	NOT ESTAB	N	Y	N	Y	N N
06	NOT ESTAB	NOT ESTAB	N				(NAPHTHA)
06	NOT ESTAB	NOT ESTAB	N				(ONTARIO)
07	NOT ESTAB	NOT ESTAB	N	Y	N	Y	N N
07	NOT ESTAB	NOT ESTAB	N				(ONTARIO)
	NOT ESTAB	NOT ESTAB	N	Y	Y	Y	N N

SARA 311/312 CATEGORIES FOR THIS PRODUCT: ACUTE= Y, CHRONIC= Y, FLAMMABILITY= Y, PRESSURE= N, REACTIVITY= N

OCCUPATIONAL EXPOSURE LIMITS HAVE BEEN ESTABLISHED FOR THE FOLLOWING MATERIALS:

REF	TLV-TWA	ACGIH	TLV-STEL	PEL-TWA	U.S. OSHA	PEL-STEL
01	100 ppm		125 ppm	100 ppm		125 ppm
02	100 ppm		150 ppm	100 ppm		150 ppm
03	2 mg/m3		NOT ESTAB	R- 5 mg/m3		NOT ESTAB
03	R- 10 MG/M3		NOT ESTAB	R- 5 mg/m3		NOT ESTAB (NUSANCDUST)
04	10 mg/m3		NOT ESTAB	10 mg/m3		NOT ESTAB
04	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (TI COMPDS)
04	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (AS TI)
05	0.02 mg/m3		NOT ESTAB	0.05 mg/m3		NOT ESTAB
05	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (CO CMPD)
05	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (AS CO)
06	300 ppm		NOT ESTAB	300 ppm		400 ppm
06	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (NAPHTHA)
06	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (ONTARIO)
07	100 ppm		NOT ESTAB	100 ppm		NOT ESTAB
07	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB (ONTARIO)
08	NOT ESTAB		NOT ESTAB	NOT ESTAB		NOT ESTAB
08			IPEL-TWA: 3 ppm			IPEL-STEL: 10 ppm

[Ceiling Limit; S- Potential Skin Absorption; R- Respirable Dust]

REF ACGIH TLV - BASIS - CRITICAL EFFECT(S)

01	irritation; CNS
02	irritation
03	pneumoconiosis
03	(NUSANCDUST)...lung
04	lung
04	(TI COMPDS) ...NOT ESTAB.
04	(AS TI) ...NOT ESTAB.
05	NOT ESTAB.
05	(CO CMPD) ...NOT ESTAB.
05	(AS CO) ...NOT ESTAB.
06	irritation; CNS
06	(NAPHTHA) ...NOT ESTAB.
06	(ONTARIO) ...NOT ESTAB.
07	irritation; narcosis; kidney
07	(ONTARIO) ...NOT ESTAB.
08	NOT ESTAB.

[ACGIH TLV BASIS - CRITICAL EFFECT(S): CNS-CENTRAL NERVOUS SYSTEM; CVS-CARDIOVASCULAR SYSTEM; CWP-COAL WORKER'S PNEUMOCONIOSIS; GI-GASTROINTESTINAL] [NOT ESTAB.= NOT ESTABLISHED = NOT APPLICABLE] [NOT ESTAB. = NOT ESTABLISHED = NOT APPLICABLE]

PRODUCT STATUS RELATIVE TO THE U.S. EPA TOXIC SUBSTANCES CONTROL ACT

All chemical substances in this product are listed on the U.S. TSCA Inventory or are otherwise exempt from TSCA Inventory reporting requirements.

SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: Harmful if swallowed.

EYE CONTACT: Causes eye irritation.

SKIN CONTACT: May cause slight skin irritation.

INHALATION: Vapor and/or spray mist may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage.

CHRONIC OVEREXPOSURE: Avoid long-term and repeated contact. This product contains titanium dioxide. Animals inhaling massive quantities of titanium dioxide dust in a long-term study developed lung tumors. Studies with humans involved in manufacture of this pigment indicate no increased risk of cancer from exposure. Potential for inhalation of titanium dioxide dusts from coatings is very limited. Since overexposures are not expected, there is no significant hazard for man. This product contains methyl ethyl ketoxime (MEKO). Studies in animals indicate that overexposure can cause adverse effects in spleen and kidney, anemia, liver cancer and cataracts. This product contains cobalt or a cobalt compound which is a possible cancer hazard based on animal data. The risk of cancer depends on the duration and level of exposure. Ethylbenzene has been reported by NTP to cause cancer in laboratory animals following a chronic (2 year) inhalation exposure. Carcinogenicity was found in the kidneys of rats and the lung and liver of mice at the 750 ppm dose level. The No Observed Effect Level (NOEL) was 75 ppm. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. High exposures to xylenes in some animal studies have been reported to cause health effects on the developing embryo and fetus. These effects were often at levels toxic to the mother. The significance of these findings to humans has not been determined.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eye watering, headaches, nausea, dizziness, and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

SECTION 4 - FIRST AID MEASURES

IMPORTANT FIRST AID INFORMATION: If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

INGESTION: Gently wipe or rinse the inside of the mouth with water. Sips of water may be given. Never give anything by mouth to an unconscious person. Contact a poison control center, emergency room or physician right away as further treatment may be necessary.

EYE CONTACT: Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

SKIN CONTACT: Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. If any symptoms persist, contact a poison control center, emergency room, or physician as further treatment may

be necessary.

INHALATION: Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

SECTION 5 - FIRE FIGHTING MEASURES

FLASHPOINT: 110 Degrees F (43 Degrees C) (PENSKY-MARTENS CLOSED CUP)

FLAMMABLE LIMITS: Lower explosion limit (LEL): 1.0

Upper explosion limit (UEL): Not available

EXTINGUISHING MEDIA: Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class II combustible liquid fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: When this product is used, the overspray and other combustible materials such as paint booth filters, paint scrapings, rags, masking materials, etc., contaminated with the coating material can present a spontaneous combustion hazard if they are not handled and disposed of properly. Wetting the contaminated materials thoroughly with water after use and placing them into a sealed metal refuse or waste container without packing them tightly will minimize the potential for spontaneous combustion. Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible explosion or ignition when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

WASTE DISPOSAL METHOD: Waste material must be disposed of in accordance with federal, state, provincial, and local environmental control regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7 - HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS: Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids.

OTHER PRECAUTIONS: Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT FOR:

EYE PROTECTION: Wear chemical-type splash goggles when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors.

SKIN PROTECTION: Wear protective clothing. Gloves should be constructed of neoprene rubber or nitrile rubber. No specific permeation/degradation testing has been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment.

RESPIRATORY PROTECTION: Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used.

OTHER EQUIPMENT: Clean contaminated clothing and shoes.

VENTILATION REQUIREMENTS: Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

[FORMULA VALUES, NOT SALES SPECIFICATIONS]

BOILING RANGE: 212- 468Degrees F

SOLUBILITY IN WATER: .2 %

VAPOR PRESSURE: 1.7 mmHg

WEIGHT/GALLON (LBS): 8.92 (U.S.)

VAPOR DENSITY: Heavier than air

pH: Not determined

% VOLATILE/VOLUME: 47.790

% SOLIDS BY WEIGHT: 65.37

SPECIFIC GRAVITY: 1.070

EVAPORATION RATE(BuOAc=100): 43

ODOR/APPEARANCE: Viscous liquid with an odor characteristic of the solvents listed in Section 2.

SECTION 10 - STABILITY AND REACTIVITY

This product is normally stable and will not undergo hazardous reactions.

INCOMPATIBILITY (MATERIALS AND CONDITIONS TO AVOID): Avoid contact with strong alkalies, strong mineral acids, or strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce the following hazardous decomposition products when exposed to extreme heat: carbon monoxide ; carbon dioxide ; oxides of aluminum ; lower molecular weight polymer fractions; Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

Hazardous Materials Identification System (HMIS) and National Fire Protection Association (NFPA) Ratings:

HMIS Rating		NFPA Rating	
HEALTH	1*	HEALTH	1
FLAMMABILITY	2	FLAMMABILITY	2
REACTIVITY	0	INSTABILITY	0

Rating System: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

TRANSPORTATION OF DANGEROUS GOODS

PROPER SHIPPING NAME: Paint

NOS TECHNICAL NAME: None

HAZARD CLASS: 3

SUBSIDIARY CLASS: None

UN NUMBER: UN1263

PACKING GROUP: III

MARINE POLLUTANT: None

USA-RQ, HAZARDOUS SUBSTANCE: Xylenes

USA-RQ, HAZARDOUS SUBSTANCE THRESHOLD SHIP WEIGHT: Xylenes > 7461.94 Pounds

USA and Canada Shipments Only- Combustible Liquid Exception: Non-bulk (≤ 119 Gallons/450 L) ground shipments can be reclassified to "not regulated" for transportation. Bulk shipments - USA Only (> 119 Gallons/450 L) can be reclassified to a Combustible Liquid.

USA Shipments Only - RQ Threshold Ship Weight: This is the total weight of this product that must be shipped to exceed the RQ quantity.

THIS IS THE END OF THE MSDS FOR: 54-330 (00250338.00354-330)

Manufactured and Supplied by:

ARCHITECTURAL FINISHES, INC.

ONE PPG PLACE

PITTSBURGH, PA 15272

ÀZ