

FasNSeal Flex



Use to vent Category II, III and **IV** gas burning appliances. Listed to UL 1738. Can only be used in or near vertical runs. Custom lengths are available for 3"-12" diameters. Minimum length of 10' for custom orders. Use with FasNSeal components only.

SIZE	20'	25'	30'	35'	50'	100'	125'	200'	CUSTOM
3"	294500	294511	294522	294533	--	--	--	294544	294590
4"	294501	294512	294523	294534	--	--	--	294545	294591
5"	294502	294513	294524	294535	--	--	294546	--	294592
5 1/2"	294503	294514	294525	294536	--	294547	--	--	294593
6"	294504	294515	294526	294537	--	294548	--	--	294594
7"	294505	294516	294527	294538	--	294649	--	--	294595
8"	294506	294517	294528	294539	294642	--	--	--	294596

SIZE	CUSTOM #
9"	294597
10"	294598
12"	294600


Male Flex Adapter



Use to connect FasNSeal rigid Vent Pipe to FasNSeal Flex at base of masonry chimney or bottom termination.

SIZE	ORDER #	STOCK #	A	B	SIZE	ORDER #	STOCK #	A	B
3"	FSASMM-3	304103	2 1/2"	3 1/2"	8"	FSASMM-8	304108	7 1/2"	8 1/2"
4"	FSASMM-4	304104	3 1/2"	4 1/2"	9"	FSASMM-9	304109	8 1/2"	9 1/2"
5"	FSASMM-5	304105	4 1/2"	5 1/2"	10"	FSASMM-10	304110	9 1/2"	10 1/2"
6"	FSASMM-6	304106	5 1/2"	6 1/2"	11"	FSASMM-11	304111	10 1/2"	11 1/2"
7"	FSASMM-7	304107	6 1/2"	7 1/2"	12"	FSASMM-12	304112	11 1/2"	12 1/2"

Female Flex Adapter



Use to connect FasNSeal Flex to FasNSeal rigid Vent Pipe at the top of the system.

SIZE	ORDER #	STOCK #	A	B	SIZE	ORDER #	STOCK #	A	B
3"	FSASMF-3	304003	2 1/2"	3 1/2"	8"	FSASMF-8	304008	7 1/2"	8 1/2"
4"	FSASMF-4	304004	3 1/2"	4 1/2"	9"	FSASMF-9	304009	8 1/2"	9 1/2"
5"	FSASMF-5	304005	4 1/2"	5 1/2"	10"	FSASMF-10	304010	9 1/2"	10 1/2"
6"	FSASMF-6	304006	5 1/2"	6 1/2"	11"	FSASMF-11	304011	10 1/2"	11 1/2"
7"	FSASMF-7	304007	6 1/2"	7 1/2"	12"	FSASMF-12	304012	11 1/2"	12 1/2"